



Under-Counter Basins Installation Instructions

To suit all Argent Under-Counter Basins

1 _____


Important: Please inspect basin/s for any imperfections prior to installation. If it is a double bowl installation, please ensure that the logos and basins are matching. No claim for imperfections or in the case of double bowls, poorly matching basins will be accepted after installation.

NB:

- a) No Cut out should be attempted without having the basin/s on hand.
- b) Use of epoxy resins will void the basin warranty – bathroom grade silicon should be used to adhere the basin to the stone top.

2 POSITIONING THE BASIN


Lay the basin face down on the back of your chosen substrate in the desired position and trace the outside contour of the basin onto the stone top. This will be used as a reference line during installation of the basin to the stone top.



Please check notes on Page 4, relative to installations with tapware located in the stone top behind the basin.

3 _____

- a) Measure the inside lip of your basin, add your desired overlap to this measurement and then draw a line running parallel and inside of the reference line of the basin (recommended overlap 8-10mm).



When you are finished, please check and compare the inside measurement of the bowl to the cut out line. If you are satisfied with the fit, cut out the slab to this inner contour line. This cut out should allow for an internal overlap/quirk of 8 to 10mm between the cut out in the slab and the basin.




Under-Counter Basins Installation Instructions

To suit all Argent Under-Counter Basins

Check the fit of the basin to the cut out, before proceeding to next step.
Polish the inside rim of the stone top as required.

4 BASIN INSTALLATION

Set up a secure area where the stone top can be laid out upside down and left for 24 hours, a void needs be left underneath the basin cut out area to allow for a visual inspection of the basin alignment with the stone top cut out. With the stone top laid out upside down, place the under-counter basin into position over the basin cut out.



Please inspect the alignment of the under-counter basin to the basin cut out in the stone top from underneath and ensure the alignment is even all the way around.

Remove the basin and ensure both the basin and the stone top are clean and free of any dirt where the silicon is to be applied.

Apply healthy beads of bathroom grade silicon adhesive to the stone top and the under-counter basin

Place the siliconed basin onto the stone top using the reference line for alignment, run an additional bead of silicon around the basin where it joins the stone top.

Double check with a visual inspection from below, of the basin alignment on the stone top. Remove any excess silicon on the inside of the basin and leave the basin and stone top to cure for a minimum of 24 hours.

Do not use epoxy resin or any rigid fixing adhesive as this may cause the basin to craze and will void the basin warranty



Under-Counter Basins Installation Instructions

To suit all Argent Under-Counter Basins

Description	Code	Nominal Inside Bowl Size	Rim Cut out size
Zen Rectangular	FC06TAL00	480x280mm	35
Zen (deep) Rectangular	FC07TAL00	490x290mm	35
Azure Oval	TPO1TAL00	410x310mm	35

All dimensions are nominal and are subject to standard manufacturing tolerances and change without notification.

IMPORTANT NOTES

If you are considering tapware in the slab behind your basin, please take into consideration when marking out tap hole location/s, the following,

- 1) Tapware has sufficient spout reach to supply water to the bowl without dripping on to the slab surface once installed. (especially with basins requiring larger rim allowance detail)
- 2) Tapware hole, relative to single lever mixers, you should allow enough clearance from the wall behind basin, so that the back of the handle does not make contact with the wall when it is in the fully on position.

If an overlap/ quirk of greater or less than the nominal dimension (up to 10mm) is desired, the rim dimension should be measured every 50mm around perimeter/ outside of the bowl, and that data transferred from the primary line drawn on the slab to the cut out template line after adding you chosen overlap dimension.

No cut out should be attempted without having the actual basin on hand.

For optimum appearance, the basin/s should be installed with the logo at the rear and the overflow hole at the front.

The manufacturer reserves the right to make technical alterations to this product.

Rim Dimensions are subject to standard manufacturing tolerances and change without notification.



For more information contact the Customer Central Technical Advice Hotline 1800 356 717